



Ambient



2M WIDE



FALCO 996M

PR: 100W X 100L
PTS: 10W X 100L



GAMBEL OAK 662M

PR: 100W X 120L
PTS: 16.6W X 120L



HAVANNA OAK 613M

PR: 100W X 150L
PTS: 16.6W X 150L



HAVANNA OAK 669D

PR: 100W X 150L
PTS: 16.6W X 150L



STOCK OAK 039M

PR: 100W X 100L
PTS: 12.5W X 100L



HAVANNA OAK 991M

PR: 100W X 150L
PTS: 16.6W X 150L



SILK OAK 916L

PR: 100W X 100L
PTS: 16.6W X 100L



robert malcolm

passionate about quality for over 140 years

WWW.ROBERTMALCOLM.CO.NZ

Commercial Vinyl Ambient


Specifications:




Slip
resistant




Thermal
resistance



Dimensional
stability



Light
fastness



Stocked in
New Zealand



15
year guarantee

Level of use ISO 10874 -	23 - 33 - 42
Total thickness -	2.50 mm
Wear layer -	0.70 mm
Wear layer PUR treatment -	PU Laquer
Total weight -	2600 g/m ²
Width -	2 m
Standard length -	25 m
Inflammability EN 13501-1 -	Bfl-S1
Critical Radiant Flux ISO 9239-1 -	8.1kW/m ²
Slip resistance DIN 51130 -	DS
Slip restraint -	R10
Residual indentation EN ISO 24343-1 -	≤ 0.10 mm
Dimensional stability EN ISO 23999-	≤ 0.40 %
Light fastness EN ISO 105 B02-	≥ 6 degrees
Underfloor heating -	Suitable
Warranty -	5 years commercial 15 years residential

- RUBBER MIGRATION: This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, Christchurch 8042, New Zealand
robertmalcolm.co.nz



robert malcolm

