



Stain Resistance



Suitable For Stairs



Antistatic



High Stitch Rating



Fade Resistance



High Twist Rating

Bedrock

Product Name:	Bedrock
Product Number:	BR01
Construction:	Tufted Textured Loop Pile
Yarn:	100% Solution Dyed Nylon
Size:	1000mm x 250mm
Tiles/Carton:	20pcs/5.0m ²
Yarn Weight:	550g/m ²
Pile Height:	3.50mm
Total Height:	8.50mm
Machine Gauge:	1/10"
Primary Backing:	Non-woven
Secondary Backing:	Comfort Back (500gms)
VOC Emission:	<0.5 mg/m hour CRI GLP (ASTM D5116-06)
Flammability:	Pass 8/8 (ASTM D-2859/FF 1-70//16CRF 1630)
Critical Radiant Flux:	5.9 kW/m ² (AS ISO 9239-1 2003)
Sound Absorption:	aw 0.5(H) (EN ISO 11654)
Static Propensity:	0.2 kV (ISO 6356)
Colourfastness:	5/5 on Grey Scale (AATCC/16)
Thermal Resistance:	0.04m K/W (ISO 8302)
Soiling Propensity:	4 (ASTM D 6540-00)
Dimensional Stability:	< 0.20% (EN 986)
Anti Allergen:	Resistant to mould & mildew
Rating:	Heavy Duty Commercial

These carpet tiles must be installed in accordance with AS/NZS 2455.1:2007.

Laying recommendation: Quarter turn or Brick.

Chair mats are mandatory under chairs with castors. This will improve appearance retention.

Please be aware that due to variation in dye lots, sample shade may vary from actual product supplied.

*The technical details and other information contained in this document are given in good faith and represent product data we believe to be accurate at the time of printing. Technical details are based on averages obtained from the manufacturing process which may vary within normal industry tolerances.