Laminate

Kaindl Aqua Pro Supreme

Specifications:















Dimensional stability

Slip resistant

Castor wheel resistant

Thermal resistance

Long lasting

Stain resistant

Light fastness

Level of use ISO 10874 -	33
Total thickness -	8 mm
Planks -	19.2 x 128.9 cm
Box planks -	9 pc/box, 2.23 m ² /box
Inflammability EN 13501-1 -	Cfl-S1
Critical Radiant Flux AS ISO 9239-1 : 2003 -	8.4 kW/m2
Abrasion resistance EN 13329 -	AC 5
Squareness & straightness EN 13329 -	≤ 0.30 mm
Sliding Friction EN13893 -	≥0.30
Impact Resistance EN 13329 -	Small Ball ≥70mm
	Big Ball ≥1000mm
Formaldehyde group EN 717-1 -	E1
Carbon Negative Production -	EDP Available
Stain resistance -	Very good
Light fastness EN ISO 105-B02-	≥6
Underfloor heating -	Suitable, max 26°C
Wear Warranty (year) -	30 Residential / 5 Commercial
Splash Area Warranty (year) -	10 Residential

- Product must be installed in accordance with the Installation Recommendations, NZ Flooring Standard NZS / AS 1884: 2013 and the Floor NZ Best Practise Guidelines Resilient Floor Coverings.
- Warranties are extended to the original purchaser of the product only and are not transferable.
- Test results confirm suitability for splash areas, however Kaindl Aqua Pro Supreme laminate is not recommended for spaces with high humidity or excessive water splash. The following areas are excluded from this warranty saunas, swimming pools, shower rooms and rooms with built in floor drains.

Please contact us on 03 366 9839 to request any samples or other product details.

international flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz 10 Establishment Drive, Christchurch 8042, New Zealand robertmalcolm.co.nz

