


L.V.T.

Moduleo Select Plank

Specifications:



Dimensional stability




Castor wheel resistant



Thermal resistance



Antistatic covering




Stain resistant



Long lasting



Great for families



Stocked in New Zealand

Level of use -	23 – 32
Total thickness -	2.35 mm
Wear layer -	0.40 mm
Wear layer PUR treatment -	Protectonite®
Total weight -	3.821 g/m ²
Planks -	19.6 x 132.0 cm (7.72" x 51.97")
Box planks -	15 pc/box, 3.9 m ² /box (41.98 ft ² /box)
Inflammability -	Bfl-S1
Scratch resistance -	Class T
Squareness & straightness -	≤ 0.35 mm
Edge detail -	Bevelled edge 4 sides
Slip resistance -	DS
Slip restraint -	R10
Residual indentation -	Norm: ≤ 0.10 mm, Average result measured ≤ 0.03 mm
Furniture leg resistance -	No cracks, no damage
Electrical resistance -	≤ 10 ⁹ Ohm
Dimensional stability -	Norm: ≤ 0.25 %, Average result measured ≤ 0.05 %
Heat insulation -	0.25 w/(m.K)
Thermal resistance R -	0.0100 m ² K/W
Electrostatic performance -	< 2 kV
Acoustic insulation -	4 dB
Castor chair resistance -	No damage to wearlayer, no delamination
Stain resistance -	Very good
Light fastness -	≥ 6
Underfloor heating -	Suitable, max 27°C
Warranty (year) -	15 Residential / 7 Commercial

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, PO Box 914, Christchurch 8140, New Zealand
robertmalcolm.co.nz


robert malcolm