



Seduction



3M WIDE



ALBUS OAK GREY

PR: 100W X 100L
PTS: 16W X 100L



ALBUS OAK HONEY

PR: 100W X 100L
PTS: 16W X 100L



ALBUS OAK LIGHT BROWN

PR: 100W X 100L
PTS: 16W X 100L



AMALFI ASHES

PR: 100W X 100L
PTS: 25W X 50L



FRENCH OAK DIM GREY

PR: 100W X 100L
PTS: 10W X 100L



FRENCH OAK MED BEIGE

PR: 100W X 100L
PTS: 10W X 100L



FRENCH OAK WHEAT

PR: 100W X 100L
PTS: 10W X 100L



ROCK GRAVEL

PR: 100W X 100L
PTS: NONE



ROCK IVORY

PR: 100W X 100L
PTS: NONE



ROCK TARMAC

PR: 100W X 100L
PTS: NONE



robert malcolm

passionate about quality for over 140 years

WWW.ROBERTMALCOLM.CO.NZ

Residential Vinyl Seduction

Specifications:




Domestic
heavy




Commercial
moderate



Slip
resistant



Reduces
noise



Light
fastness



Thermal
resistance



Chemical
resistant



10
year guarantee


	400 Quality	450 Quality
European classification EN ISO 10874 -	23 / 31	23 / 31
Total thickness -	4.00 mm	4.50 mm
Wear layer -	0.25 mm	0.30 mm
Total weight -	2050 g/m ²	3000 g/m ²
Width -	3 m	3 m
Slip resistance DIN 51130 -	R10	R10
Inflammability -	Cfl-S1	Cfl-S1
Critical radiant flux ISO 9239.1:2010 -	7.50 KW/m ²	7.20 KW/m ²
Acoustical insulation EN ISI 717-2 -	21 dB	20 dB
Light fastness ISO 105-B02 -	≥ 6	≥ 6
Underfloor heating -	Suitable (max 27°C)	Suitable (max 27°C)
Thermal resistance ISO 10456 -	0.05 m ² /kW	0.07 m ² /kW
Resistance to household chemicals -	OK	OK
Residual indentation EN ISO 24343-1	≤ 0.20 mm	≤ 0.35 mm
Dimensional stability EN ISO 23999 -	≤ 0.15	≤ 0.15
Formaldehyde group EN 717-1 -	E1	E1
Total VOC emissions EN 16516 -	Gold	Gold
Warranty (year) -	10 years (Residential use)	10 years (Residential use)

- **RUBBER MIGRATION:** This is a condition that can cause vinyl to discolour. Migration occurs when latex or rubber products such as shoes, rubber backed mats or rubber soled slippers come into contact with vinyl over a period of time. This is not a manufacturing fault and therefore is not covered under our warranties.
- Warranties are extended to the original purchaser of the product only and are not transferable.

Please contact us on 03 366 9839 to request any samples or other product details.

international
flooring solutions

p 03 366 9839 e office@robertmalcolm.co.nz
10 Establishment Drive, Christchurch 8042, New Zealand
robertmalcolm.co.nz


robert malcolm

